

## GAMAFLEX 40-JB GAMAFLEX 40-OB



### Application

As control and supply cables for control units in metal working machines, transportation equipment, production lines, as well as for control and measuring systems at rated voltage  $U_0/U$  300/500 V .

The cables are suitable for flexible applications for free, non-continuous returning movement, without tensile load as well as for fixed laying.

They are oil and chemical resistant under normal operation conditions and are suitable for use in dry, damp or wet interiors. These cables may only be laid outdoors with UV-protection and in observance of the temperature range.

### Technical data

- manufactured acc. to the technical specification TS 03-14-02 A of GAMAKABEL
- rated voltage  $U_0/U$ : 300/500 V
- test voltage: 4 kV
- insulation resistance at 70 °C: min 20 GΩ x cm
- maximum conductor temperature: + 70 °C
- max. conductor temperature at short circuit for 5 s : +160 °C
- temperature range:  
occasional flexing: - 15 °C\*\* to +70 °C; fixed installation : -40 °C to +80 °C  
\*\* Tested according EN 60811-1-4: cold bending test, impact resistance test at low temperatures, elongation test at low temperatures.
- minimum temperature during installation: - 5 °C
- minimum bending radius for: mobile - 15 D; fixed - 4 D (D - outer cable diameter)
- flame test: flame-retardant acc. to IEC 60332-1
- sheath colour: silver grey - RAL 7001

### Cable design

- copper conductors class 5 according to IEC 60228
- insulation: PVC compound type TI2 according to HD 21.1
- sheath: PVC compound type TM2 according to HD21.1
- **GAMAFLEX 40-OB** - without green-yellow protective conductor
- **GAMAFLEX 40-JB** - with green-yellow protective conductor in the outer layer

### Core identification

- up to 5 cores - color identification according HD308 S2
- above 5 cores - color identification according TS 03-14-02 A

No of cores	Cables without green-yellow protective conductor	Cables with green-yellow protective conductor
2	brown, blue	-
3	brown, black, grey	green-yellow, blue, brown
4	blue, brown, black, grey	green-yellow, brown, black, grey
5	blue, brown, black, grey, black	green-yellow, blue, brown, black, grey
6	white, black, blue, brown, grey, red	green-yellow, white, black, blue, brown, grey
7	white, black, blue, brown, grey, red, violet	green-yellow, white, black, blue, brown, grey, red
8	white, black, blue, brown, grey, red, violet, pink	green-yellow, white, black, blue, brown, grey, red, violet
9	white, black, blue, brown, grey, red, violet, pink, orange	green-yellow, white, black, blue, brown, grey, red, violet, pink
10	-	green-yellow, white, black, blue, brown, grey, red, violet, pink, orange

# GAMAFLEX 40-JB

## GAMAFLEX 40-OB

Number of Conductors and Cross Section No x mm <sup>2</sup>	Outer Diameter mm	Copper Weight kg/km	Cable Weight kg/km		Number of Conductors and Cross Section No x mm <sup>2</sup>	Outer Diameter mm	Copper Weight kg/km	Cable Weight kg/km
2 x 0,5	4,7	9,6	35		2 x 2,5	7,6	48,0	105
3 x 0,5	4,9	14,4	42		3 x 2,5	8,0	72,0	133
4 x 0,5	5,3	19,2	55		4 x 2,5	9,0	96,0	175
5 x 0,5	6,0	24,0	66		5 x 2,5	9,8	120,0	214
6 x 0,5	6,5	28,8	75		6 x 2,5	10,9	144,0	246
7 x 0,5	6,5	33,6	79		7 x 2,5	10,9	168,0	265
8 x 0,5	7,7	38,4	100		8 x 2,5	13,0	192,0	346
9 x 0,5	8,1	43,2	114		9 x 2,5	13,9	216,0	393
10 x 0,5	8,2	48,0	109		10 x 2,5	14,3	240,0	386
2 x 0,75	5,1	14,4	45		2 x 4,0	8,6	76,8	150
3 x 0,75	5,4	21,6	57		3 x 4,0	9,3	115,2	195
4 x 0,75	6,1	28,8	69		4 x 4,0	10,7	153,6	244
5 x 0,75	6,7	36,0	84		5 x 4,0	11,4	192,0	307
6 x 0,75	7,2	43,2	97		6 x 4,0	12,6	230,4	360
7 x 0,75	7,2	50,4	103		7 x 4,0	12,6	268,8	391
8 x 0,75	8,6	57,6	130		2 x 6,0	10,6	115,2	224
9 x 0,75	9,3	64,8	159		3 x 6,0	11,2	172,8	287
10 x 0,75	9,5	72,0	153		4 x 6,0	12,5	230,4	367
2 x 1,0	5,4	19,2	54		5 x 6,0	13,9	288,0	460
3 x 1,0	5,7	28,8	66		6 x 6,0	15,4	345,6	537
4 x 1,0	6,5	38,4	81		7 x 6,0	15,4	403,2	583
5 x 1,0	7,1	48,0	98		2 x 10,0	15,0	192,0	392
6 x 1,0	7,9	57,6	113		3 x 10,0	15,9	288,0	503
7 x 1,0	7,9	67,2	121		4 x 10,0	17,9	384,0	642
8 x 1,0	9,4	76,8	162		2 x 16,0	16,8	307,2	626
9 x 1,0	9,9	86,4	182		3 x 16,0	18,0	460,8	785
10 x 1,0	10,1	96,0	278		4 x 16,0	19,9	614,4	995
2 x 1,5	6,1	28,8	69		2 x 25,0	20,6	480,0	943
3 x 1,5	6,5	43,2	85		3 x 25,0	22,0	720,0	1186
4 x 1,5	7,0	57,6	106		4 x 25,0	24,4	960,0	1506
5 x 1,5	7,9	72,0	129					
6 x 1,5	8,6	86,4	148					
7 x 1,5	8,6	100,8	159					
8 x 1,5	10,5	115,2	211					
9 x 1,5	11,0	129,6	239					
10 x 1,5	11,5	144,0	234					

\* GAMAFLEX 40-OB has up to 9 conductors